

R410A

Cassette Split



AIR CONDITIONER

www.jet-air.co.za

- Fresh Air Intake
- Silent
- Auto Restart Function
- Self-diagnosis Function
- Sleep Mode



Cassette Split Type Technical Specifications



- Fresh Air Intake
- Self-diagnosis Function
- Auto Restart Function
- Silent
- Sleep Mode

Model	Indoor		JASA-Ca-H12A4/ R1C7-B7	JASA-Ca-H18A4/ R1C7-B7	JASA-Ca-H24A4/ R1EB-B7	JASA-Ca-H36A4/ R1EB-B7	JASA-Ca-H36A5/ R1EB-B7	JASA-Ca-H48A5/ R1EB-B7	JASA-Ca-H60A5/ R1EB-B7	
	Outdoor		JASA-H12A4/ R1(T)-B7	JASA-H18A4/ R1(T)-B7	JASA-H24A4/ R1(T)-B7	JASA-H36A4/ R1(T)-B7	JASA-H36A5/ R1(T)-B7	JASA-H48A5/ R1(T)-B7	JASA-H60A5/ R1(T)-B7	
Power Supply		V~, Hz, Ph	220~240, 50, 1	220~240, 50, 1	220~240, 50, 1	220~240, 50, 1	380~415, 50, 3	380~415, 50, 3	380~415, 50, 3	
Capacity	Cooling	Btu/h	12000	18000	24000	36000	36000	48000	60000	
		kw	3.60	5.30	7.20	10.6	10.60	14.00	17.60	
	Heating	Btu/h	13307	19790	27569	40000	39920	52886	63122	
		kw	3.90	5.80	8.08	11.7	11.70	15.50	18.50	
Electric Data	Rated Cooling Power Input	kw	1.19	1.76	2.39	3.77	3.77	4.87	5.71	
	Rated Heating Power Input	kw	1.20	1.80	2.50	3.5	3.50	5.13	6.00	
	Rated Cooling Current	A	5.49	8.08	11.06	17.3	6.76	8.88	10.42	
	Rated Heating Current	A	5.63	8.27	11.59	16.6	6.28	9.33	10.88	
Performance	EER/COP	w/w	3.03/3.25	3.01/3.22	3.01/3.23	2.81/3.34	2.81/3.34	2.87/3.02	3.08/3.08	
Indoor Unit	Indoor Air Flow (Hi/Mi/Lo)	m ³ /h	620/496/434	900/720/630	1300/1040/910	1500/1200/1050	1500/1200/1050	1800/1440/1260	1800/1440/1260	
	Noise Level (Hi/Mi/Lo)	dB(A)	41/38/32	41/38/32	45/42/36	48/45/39	48/45/39	50/47/41	50/47/41	
	Dimension (W×D×H)	Net (Body)	mm	615×615×263	615×615×263	835×835×250	835×835×250	835×835×250	835×835×290	835×835×290
		Packing (Body)	mm	700×700×330	700×700×330	910×910×310	910×910×310	910×910×310	910×910×350	910×910×350
		Net (Panel)	mm	650×650×55	650×650×55	950×950×55	950×950×55	950×950×55	950×950×55	950×950×55
		Packing (Panel)	mm	710×710×80	710×710×80	1000×1000×100	1000×1000×100	1000×1000×100	1000×1000×100	1000×1000×100
	Weight	Net/Gross (Body)	kg	17.5/21.5	18/22	24/27.5	24/27.5	24/27.5	26.5/30.5	26.5/30.5
		Net/Gross (Panel)	kg	3/5	3/5	5/7	5/7	5/7	5/7	5/7
	Outdoor Unit	Noise Level	dB(A)	53	55	60	60	62	60	60
		Dimension (W×D×H)	Net	mm	800×286×530	800×286×530	822×302×655	903×354×857	903×354×857	940×368×1366
Packing			mm	920×400×620	920×400×620	945×430×725	1030×410×980	1030×410×980	1080×460×1500	1080×460×1500
Weight		Net/Gross	kg	34/37	38/41	50/54	72/83	71/81	101/112	102/113
Refrigerant Pipe	Liquid Side	inch	1/4	1/4	3/8	3/8	3/8	3/8	3/8	
	Gas Side	inch	1/2	1/2	5/8	5/8	5/8	3/4	3/4	
	Max. Length	m	15	20	30	50	50	50	50	
	Max. Height	m	10	15	15	30	30	30	30	

Remarks: Cooling capacities are based on indoor air temp. 27°C DB, 19°C WB and outdoor air temp. 35°C DB, 24°C WB. The above specifications are subject to change without prior notice for product improvement.



12~24K



36K



48~60K

E&OE

www.jet-air.co.za



Remark: The above designs and specifications are subject to change of product improvement without prior notice.