



Ducted Inverter

- Meeting requirement from 12 000 btu/h to 60 000 btu/h with excellent and energy saving performance.
- Universal outdoor units with and diversified indoor units satisfy customized decoration.
- Free combination and easy installation.
- Long distance monitoring, weekly timer and low ambient cooling are optional.



R410A

INVERTER

A Energy
Efficiency
Class
A

Southern Africa: Sales/Distribution solely by JA-SA import & export
www.jet-air.co.za



Ducted Inverter



Model No.	Outdoor	JASA-H12A4/FIU	JASA-H18A4/FIU	JASA-H24A4/FIU	JASA-H30A4/FIU	JASA-H36A4/FIU
Model No.	Indoor	JASA-Hi-H12A4/FI	JASA-Hi-H18A4/FI	JASA-Hi-H24A4/FI	JASA-Hi-H30A4/FI	JASA-Hi-H36A4/FI
Power supply	Outdoor	220-240V-1-50	220-240V-1-50	220-240V-1-50	220-240V-1-50	220-240V-1-50
Power supply	Indoor	220-240V-1-50	220-240V-1-50	220-240V-1-50	220-240V-1-50	220-240V-1-50
Cooling capacity	BTU/H	11942	17060	23884	28320	34120
Cooling input	kW	1.09	1.55	2.18	2.67	3.2
Cooling current	A	5.4	7.5	10.1	12.4	15
Heating capacity	BTU/H	12966	19107	27296	31390	40944
Heating input	kW	1.09	1.55	2.21	2.57	3.4
Heating current	A	4.9	7.4	10.2	12	15.5
Indoor dimensions	mm (WxDxH)	998x721x266	998x721x266	1239x558x268	1239x558x268	1226x775x290
Outdoor dimensions	mm (WxDxH)	848x320x540	955x396x700	980x427x790	980x427x790	1107x440x1100
Indoor packing	mm (WxDxH)	1123x798x323	1123x798x323	1348x597x283	1348x597x283	1338x877x305
Outdoor packing	mm (WxDxH)	881x363x595	1029x458x750	1083x448x855	1083x448x855	1158x493x1235
Indoor Weight	N. W./G.W. Kg	33/38	33/38	34/39	34/39	46/53
Outdoor Weight	N. W./G.W. Kg	34/37	47/50	67/72	71/76	92/100
Liquid pipe	inch (mm)	Φ1/4 (6.35)	Φ1/4 (6.35)	Φ3/8 (9.52)	Φ3/8 (9.52)	Φ3/8 (9.52)
Gas pipe	inch (mm)	Φ3/8 (9.52)	Φ1/2 (12.7)	Φ5/8 (15.9)	Φ5/8 (15.9)	Φ5/8 (15.9)

Model No.	Outdoor	JASA-H36A5/FIU	JASA-H42A4/FIU	JASA-H42A5/FIU	JASA-H48A4/FIU	JASA-H48A5/FIU	JASA-H60A5/FIU
Model No.	Indoor	JASA-Hi-H36A4/FI	JASA-Hi-H42A4/FI	JASA-Hi-H42A4/FI	JASA-Hi-H48A4/FI	JASA-Hi-H48A4/FI	JASA-Hi-H60A4/FI
Power supply	Outdoor	380-415V-3-50	220-240V-1-50	380-415V-3-50	220-240V-1-50	380-415V-3-50	380-415V-3-50
Power supply	Indoor	220-240V-1-50	220-240V-1-50	220-240V-1-50	220-240V-1-50	220-240V-1-50	220-240V-1-50
Cooling capacity	BTU/H	34120	39238	39238	47768	47768	54592
Cooling input	kW	3.12	4	4	4.7	4.8	5.6
Cooling current	A	5.6	18.6	6.8	21.8	8.2	9.8
Heating capacity	BTU/H	40944	46062	46602	52886	52886	56298
Heating input	kW	3.32	3.9	3.9	4.4	4.4	4.57
Heating current	A	6	18.1	6.7	20.4	7.6	8
Indoor dimensions	mm (WxDxH)	1226x775x290	1226x775x290	1226x775x290	1340x750x350	1340x750x350	1340x750x350
Outdoor dimensions	mm (WxDxH)	1107x440x1100	958x412x1349	958x412x1349	958x412x1349	958x412x1349	1085x427x1365
Indoor packing	mm (WxDxH)	1338x877x305	1338x877x305	1338x877x305	1420x837x455	1420x837x455	1420x837x455
Outdoor packing	mm (WxDxH)	1158x493x1235	1043x453x1500	1043x453x1500	1043x453x1500	1043x453x1500	1143x478x1505
Indoor Weight	N. W./G.W. Kg	46/53	46/53	46/53	56/65	56/65	57/69
Outdoor Weight	N. W./G.W. Kg	98/106	95/105	108/118	108/118	114/124	126/138
Liquid pipe	inch (mm)	Φ3/8 (9.52)	Φ3/8 (9.52)	Φ3/8 (9.52)	Φ3/8 (9.52)	Φ3/8 (9.52)	Φ3/8 (9.52)
Gas pipe	inch (mm)	Φ5/8 (15.9)	Φ5/8 (15.9)	Φ5/8 (15.9)	Φ5/8 (15.9)	Φ5/8 (15.9)	Φ3/4 (19.05)

Southern Africa: Sales/Distribution solely by JA-SA import & export
www.jet-air.co.za